



DELL EMC POWERSWITCH N3200-ON SERIES SWITCHES

High performance Open networking 1GbE and 10GbE Multigigabit switches for modern campus networks

The N3200 switch series offers power-efficient and resilient 1GbE and 1/2.5/5/10GbE Multigigabit range of switching solution for advanced Layer 3 distribution for offices and campus networks. The series has high-performance capabilities and wire-speed performance utilizing a non-blocking architecture to easily handle unexpected traffic loads. Use dual internal hot-swappable 80PLUS Platinum certified power supplies for high availability and power efficiency. The switches offer simple management and scalability via an 400Gbps (full duplex) high-availability stacking architecture that allows management of up to 12 switches from a single IP address.

Modernize campus network architectures

Modernize campus network architectures with a power-efficient and resilient 1/2.5/5/10GbE switching solution with dense options of 802.3at (30W) or 802.3bt (60W/90W) PoE solutions to deliver clean power to wide range network devices such as wireless access points (APs), Voice-over-IP (VoIP) handsets, video conferencing systems, security cameras, LED luminaires and many more.

Achieve high availability and full bandwidth utilization with Multichassis Link Aggregation (MLAG). N3200 series switches support MLAG to create active/active loop-free redundancy without spanning tree. Server rooms can deliver reliable server and storage connectivity with features to help save time and avoid configuration errors. N3200 supports VRF-lite, allowing it to be partitioned into multiple virtual routers with isolated control and data planes on the same physical switch. For greater interoperability in multivendor networks, N3200 switches offer the latest open-standard protocols.

Leverage familiar tools and practices

All N-Series switches include Dell EMC Networking OS6, designed for easier deployment, greater interoperability and a lower learning curve for network administrators. OS6 common command line interface (CLI) and graphic user interface (GUI) are intuitive, so skilled network administrators can get productive quickly. N3200 switches also support the Open Network Install Environment (ONIE), enabling installation of alternate network operating systems.

Deploy with confidence at any scale

N3200 series switches help create performance assurance with a data rate up to 1560Gbps (full duplex) and a forwarding rate up to 2167Mpps. Scale easily with built-in rear stacking ports. Switch stacks of up to 624 1/2.5/5/10GbE/25GbE ports can be managed from a single screen using the highly available stacking architecture for high-density aggregation with seamless redundant availability. The N-series switches' lifetime warranty covers software upgrades, hardware repair or replacement, and optics and cables purchased with the switch.¹

¹ Select Networking products carry a Lifetime Limited Warranty with Basic Hardware Service (repair or replacement) for life. Repair or replacement does not include troubleshooting, configuration, or other advanced service provided by Dell EMC ProSupport. See details at <https://www.dell.com/en-us/work/shop/networkingwarranty/cp/networkingwarranty>

² Can be used if enabled by ON partner network operating system.

Hardware, performance and efficiency

- 1GbE Switches: 1RU switches with up to 48 line-rate 1GbE ports of copper or fiber, and four integrated 10GbE SFP+ ports. PoE variants with up to 48 ports of 802.3at (30W) PoE.
- Multigig Switches: 1RU switches with up to 48 line-rate 1G/2.5G/5G/10GbE copper ports with four integrated 25GbE SFP28 ports. PoE variants with up to 48 ports of 802.3bt (90W) PoE.
- 400Gbps stacking bandwidth using two 100GbE QSFP28 integrated rear stacking ports.
- Available with dual 80PLUS Platinum certified hot swappable internal power supplies. Optional external power supply to extend PoE budgets on specific models.
- Variable speed fan operation helps decrease cooling and power costs.
- Energy-Efficient Ethernet and lower power PHYs reduce power to inactive ports and idle links, providing energy savings from the power cord to the port.
- Dell EMC Fresh Air compliance for operation in environments up to 113°F (45°C) reduces cooling costs.

Deploying, configuring and managing

- USB auto-configuration rapidly deploys the switch without complex TFTP configurations or sending technical staff to remote offices.
- Management via an intuitive and familiar CLI, embedded web server (GUI), SNMP-based management console application (including Dell EMC OpenManage Network Manager), Telnet or serial connection.
- Private VLAN extensions and Private VLAN Edge support.
- AAA authorization, TACACS+ accounting and RADIUS support for comprehensive secure access support.
- Authentication tiering allows network administrators to tier port authentication methods such as 802.1x, MAC Authentication Bypass and Captive Portal in priority order so that a single port can provide flexible access and security.
- Achieve high availability and full bandwidth utilization with MLAG and support firmware upgrades without taking the network offline.
- Layer 3 Advanced IPv4 and IPv6 functionality including BGP, VRF, BFD, PIM-SM/DM/SSM, IGMP/MLD, RIPv1/v2, OSPFv2/v3
- VXLAN support in hardware only ²
- MACsec support in N3248PXE-ON hardware only ²

Product	Description
<p>N3200 series</p>	<p>OS6 Options (with pre-installed OS6 NOS)</p> <ul style="list-style-type: none"> • N3208PX-ON IO/PS Airflow, with OS6: 4x RJ45 10M/100M/1G/2.5G/5G 802.3bt (up to 90W) PoE auto-sensing ports, 4x 10M/100M/1000Mb 802.3bt (up to 90W) PoE auto-sensing ports, 2x 10G SFP+ ports, 1x 320W AC PSU included • N3224T-ON IO/PS Airflow, with OS6: 24x RJ45 10/100/1000Mb auto-sensing ports, 4x 10G SFP+ ports, 2X 100G QSFP28 ports, 1x 550W AC PSU included • N3224T-ON PS/IO Airflow, with OS6: 24x RJ45 10/100/1000Mb auto-sensing ports, 4x 10G SFP+ ports, 2X 100G QSFP28 ports, 1x 550W AC PSU included • N3224F-ON IO/PS Airflow, with OS6: 24x 1G SFP, 4x 10G SFP+ ports, 2X 100G QSFP28 ports, 1x 550W AC PSU included • N3224P-ON IO/PS Airflow, with OS6: 24x RJ45 10/100/1000Mb 802.3at (up to 30W) PoE auto-sensing ports, 4x 10G SFP+ ports, 2X 100G QSFP28 ports, 1x 1050W AC PSU included • N3224PX-ON IO/PS Airflow, with OS6: 24x RJ45 10M/100M/1G/2.5G/5G/10G 802.3bt (up to 90W) PoE auto-sensing ports, 4x 25G SFP28 ports, 2X 100G QSFP28 ports, 1x 1600W AC PSU included • N3248TE-ON IO/PS Airflow, with OS6: 48x RJ45 10/100/1000Mb auto-sensing ports, 4x 10G SFP+ ports, 2X 100G QSFP28 ports, 1x 550W AC PSU included • N3248TE-ON PS/IO Airflow, with OS6: 48x RJ45 10/100/1000Mb auto-sensing ports, 4x 10G SFP+ ports, 2X 100G QSFP28 ports, 1x 550W AC PSU included • N3248P-ON IO/PS Airflow, with OS6: 48x RJ45 10/100/1000Mb 802.3at (up to 30W) PoE auto-sensing ports; 4x 10G SFP+ ports, 2X 100G QSFP28 ports, 1x 1050W AC PSU included • N3248X-ON IO/PS Airflow, with OS6: 48x RJ45 10M/100M/1G/2.5G/5G/10G auto-sensing ports, 4x 25G SFP28 ports, 2X 100G QSFP28 ports, 1x 550W AC PSU included • N3248X-ON PS/IO Airflow, with OS6: 48x RJ45 10M/100M/1G/2.5G/5G/10G auto-sensing ports, 4x 25G SFP28 ports, 2X 100G QSFP28 ports, 1x 550W AC PSU included • N3248PXE-ON IO/PS Airflow, with OS6: 48x RJ45 10M/100M/1G/2.5G/5G/10G 802.3bt (up to 90W) PoE auto-sensing ports; 4x 25G SFP28 ports, 2X 100G QSFP28 ports, 1x 1600W AC PSU included <p>NO-OS Options (no pre-installed NOS, recommended for use with Enterprise SONiC Distribution by Dell Technologies)</p> <ul style="list-style-type: none"> • N3248TE-ON IO/PS Airflow, NO-OS: 48x RJ45 10/100/1000Mb auto-sensing ports, 4x 10G SFP+ ports, 2X 100G QSFP28 ports, 1x 550W AC PSU included ² • N3248TE-ON PS/IO Airflow, NO-OS: 48x RJ45 10/100/1000Mb auto-sensing ports, 4x 10G SFP+ ports, 2X 100G QSFP28 ports, 1x 550W AC PSU included ² <p>OS10 Options (with pre-installed OS10 NOS)</p> <ul style="list-style-type: none"> • N3248TE-ON IO/PS Airflow, with OS10: 48x RJ45 10/100/1000Mb auto-sensing ports, 4x 10G SFP+ ports, 1x 550W AC PSU included • N3248TE-ON PS/IO Airflow, with OS10: 48x RJ45 10/100/1000Mb auto-sensing ports, 4x 10G SFP+ ports, 1x 550W AC PSU included
<p>Power cords</p>	<p>C15 to NEMA 5-15, 1.8M (N3208PX-ON only) C13 to NEMA 5-15, 3M (all other N3200 platforms) C13 to C14, 2M (all other N3200 platforms)</p>
<p>Power shelves (optional)</p>	<ul style="list-style-type: none"> • MPS-1S Shelf, External power shelf to hold 1 PSU (any of 1050W AC, 1600W AC, 2000W AC, 1300W DC), Extends PoE budget for N3224PX-ON, N3248P-ON, N3248PXE-ON ³ • MPS-3S Shelf, External power shelf to hold up to 3 PSUs (any combination of 1050W AC or 1600W AC or 2000W AC PSUs, or up to three 1300W DC PSUs), Extends PoE budget for N3224PX-ON, N3248P-ON, N3248PXE-ON ³

Product	Description
<p>Power supplies (optional)</p>	<ul style="list-style-type: none"> • 320W AC external power adapter, adds redundancy and/or extends PoE budget for N3208PX-ON • 550W AC hot swappable with IO/PS airflow, adds redundancy to N3224T-ON, N3224F-ON, N3248TE-ON, N3248X-ON • 550W AC hot swappable with PS/IO airflow, adds redundancy to N3224T-ON, N3248TE-ON, N3248X-ON • 1050W AC hot swappable, adds redundancy and/or extends PoE budget for N3224P-ON, N3248P-ON. Also used with MPS-1S shelf, MPS-3S Shelf • 1600W AC hot swappable, adds redundancy and/or extends PoE budget for N3224PX-ON, N3248PXE-ON. Also used with MPS-1S shelf, MPS-3S Shelf • 2000W AC hot swappable, extends PoE budget, used with MPS-1S Shelf, MPS-3S Shelf ³ • 550W DC hot swappable with IO/PS airflow, adds redundancy to N3224T-ON, N3224F-ON, N3248TE-ON, N3248X-ON • 550W DC hot swappable with PS/IO airflow, adds redundancy to N3224T-ON, N3248TE-ON, N3248X-ON • 1300W DC hot swappable, adds redundancy and/or extends PoE budget for N3224P-ON, N3248P-ON, N3224PX-ON, N3248PXE-ON ³
<p>Optics</p>	<p>Transceiver, SFP, 1000BASE-T ⁴</p> <p>Transceiver, SFP, 1000BASE-SX ⁴</p> <p>Transceiver, SFP, 1000BASE-LX ⁴</p> <p>Transceiver, SFP, 1000BASE-ZX ⁴</p> <p>Transceiver, SFP+ 10GbE, USR (MMF upto 100m) ⁵</p> <p>Transceiver, SFP+ 10GbE, SR (MMF upto 400m) ⁵</p> <p>Transceiver, SFP+ 10GbE, LRM (MMF 220m) ⁵, for SFP+ ports only</p> <p>Transceiver, SFP+ 10GbE, LR (SMF 10 km) ⁵</p> <p>Transceiver, SFP+ 10GbE, ER SMF 40 km) ⁵</p> <p>Transceiver, SFP+ 10GbE, ZR (SMF 80 km) ⁵</p> <p>Transceiver, SFP+ 10GbE, BASE-T GEN2 ⁵</p> <p>Transceiver, SFP28 25GbE, LR</p> <p>Transceiver, SFP28 25GbE, SR-NOF</p> <p>Transceiver, SFP28 25GbE, ESR</p> <p>Transceiver, QSFP28 100GbE, Q28-100G-SR4-HG</p> <p>Transceiver, QSFP28 100GbE, Q28-100G-LR4-G3</p>
<p>Cables</p>	<p>10GbE, SFP+ to SFP+, Passive DAC (0.5M, 1M, 2M, 3M, 5M, 7M) ⁵</p> <p>10GbE, SFP+ to SFP+, Active optical (2M, 3M, 5M, 7M, 10M,15M, 20M) ⁵</p> <p>25GbE, SFP28 to SFP28, Passive DAC (1M, 2M, 3M, 5M)</p> <p>25GbE, SFP28 to SFP28, Active optical (7M, 10M,15M, 20M)</p> <p>100GbE, QSFP28 to QSFP28, Passive DAC (0.5M, 1M, 2M, 3M, 5M)</p>
<p>Fans (spare)</p>	<p>Fan module, IO to PSU Airflow</p> <p>Fan module, PSU to IO Airflow (for N3224T-ON, N3248TE-ON, N3248X-ON only)</p>

³ Planned in Roadmap

⁴ Auto-negotiation not supported, using 1G optics require manual configuration and all 4x10G SFP+ or 4x25G SFP28 ports to be set to same speed. 100M speed not supported.

⁵ Auto-negotiation not supported, using 10G cables or optics require manual configuration and all 4x25G SFP28 ports to be set to same speed. 100M/1G speed not supported.

Hardware specifications

Physical

2 integrated rear 100GbE QSFP28 stacking ports (except N3208PX-ON)
Out-of-band management port (10/100/1000BASE-T)
USB (Type A) port for configuration via USB flash drive
MicroUSB (Type B) console port (MicroUSB to USB connector cable included)
RJ45 console port with RS232 signaling (RJ-45 to female DB-9 connector cable included)
Auto-negotiation for speed and flow control
Auto-MDI/MDIX, port mirroring
Flow-based port mirroring Broadcast storm control
Energy-Efficient Ethernet per port settings
Redundant variable speed fans
Air flow: I/O to power supply
Power supply:
Integrated 320W (N3208PX-ON), 550W (N3224T-ON, N3224F-ON, N3248TE-ON, N3248X-ON), 1050W (N3224P-ON, N3248P-ON), 1600W (N3224PX-ON, N3248PX-ON)
Dual firmware images on-board
Switching engine model: Store and forward

Chassis

Size (1RU, H x W x D):
N3208PX-ON: 1.71 in x 11 in x 12.28 in;
All other models: 1.71 in x 17.09 in x 15.75 in (power supply/fan tray handle adds add'l 1.18 in)
Approximate weight (Switch with 1 PSU installed):
8.44lbs/3.83kg (N3208PX-ON), 13.75lbs/6.24kg (N3224T-ON), 14.25lbs/6.46kg (N3224F-ON), 15.6lbs/7.08kg (N3224P-ON), 16lbs/7.26kg (N3224PX-ON), 15.4lbs/6.99kg (N3248TE-ON), 16.7lbs/7.57kg (N3248P-ON), 16.1lbs/7.3kg (N3248X-ON), 17.6lbs/7.98kg (N3248PX-ON)
2-post rack mounting kit

Environmental

Power supply efficiency: 87% or better in all operating modes
Max. thermal output (BTU/hr):
2821 (N3208PX-ON), 686 (N3224T-ON), 764 (N3224F-ON), 3220 (N3224P-ON), 9344 (N3224PX-ON), 723 (N3248TE-ON), 5719 (N3248P-ON), 1637 (N3248X-ON), 18224 (N3248PX-ON)
Power consumption max (watts):
900 (N3208PX-ON), 201 (N3224T-ON), 224 (N3224F-ON), 944 (N3224P-ON), 2740 (N3224PX-ON), 212 (N3248TE-ON), 1677 (N3248P-ON), 480 (N3248X-ON), 5344 (N3248PX-ON)
Operating temperature: 32° to 113°F (0° to 45°C)
Operating relative humidity: 95%
Storage temperature: -40° to 158°F (-40° to 70°C)
Storage relative humidity: 95%

Performance

CPU memory: 4GB
SSD: 8GB (32GB for N3248TE-ON)
Packet buffer memory:
8MB (4MB for N3208PX-ON and 32MB for N3248X-ON and N3248PX-ON)
Switch fabric capacity (full-duplex):
88Gbps (N3208PX-ON), 528Gbps (N3224T-ON, N3224F-ON, N3224P-ON), 576Gbps (N3248TE-ON, N3248P-ON),

1080Gbps (N3224PX-ON), 1560Gbps (N3248X-ON, N3248PX-ON)
Forwarding rate:
122Mpps (N3208PX-ON), 733Mpps (N3224T-ON, N3224F-ON, N3224P-ON), 800Mpps (N3248TE-ON, N3248P-ON), 1500Mpps (N3224PX-ON), 2167Mpps (N3248X-ON, N3248PX-ON)
Line-rate Layer 2 switching: All (non-blocking)
Line-rate Layer 3 routing: All (non-blocking)

Network Operating System specifications

Software specifications listed below are applicable for OS6. For detailed specifications of NOS, please contact your Dell Technologies representative.

Scaling performance

MAC addresses: 32K
Link aggregation:
128 LAG groups, 144 dynamic ports per stack, 8 member ports per LAG
Priority queues per port: 8
Static routes: 1,024 (IPv4)/1,024 (IPv6)
Dynamic routes: 8,158 (IPv4)/4,096 (IPv6)
OSPF routing interfaces: 8,158
RIP routing interfaces: 512
ECMP next hops per route: 16
ECMP groups: 1024
VLAN routing interfaces: 128
VLANs supported: 4,094
Protocol-based VLANs: Supported
Multicast forwarding entries:
1,536 (IPv4), 512 (IPv6)
ARP entries: 6,144
NDP entries: 2,560
Access control lists (ACL): Supported
MAC and IP-based ACLs: Supported
Time-controlled ACLs: Supported
Max number of ACLs: 100
Max ACL rules system-wide: 3,914
Max rules per ACL: 1,023
Max ACL rules per interface (IPv4):
1,023 (ingress), 511 (egress)
Max ACL rules per interface (IPv6):
1,021 (ingress), 509 (egress)
Max VLAN interfaces with ACLs applied: 24

IEEE compliance

802.1AB LLDP
Dell Voice VLAN
Dell ISDP
802.1D Bridging, Spanning Tree
802.1p Ethernet Priority (User Provisioning and Mapping)
Dell Adjustable WRR and Strict Queue Scheduling
802.1Q VLAN Tagging, Double VLAN Tagging, GVRP
802.1S Multiple Spanning Tree (MSTP)
802.1v Protocol-based VLANs
802.1W Rapid Spanning Tree (RSTP)
Dell RSTP-Per VLAN
Dell Spanning tree optional features: STP root guard, BPDU guard, BPDU filtering
802.1X Network Access Control, Auto VLAN
802.2 Logical Link Control
802.3 10BASE-T
802.3ab Gigabit Ethernet (1000BASE-T)
802.3ac Frame Extensions for VLAN Tagging
802.3ad Link Aggregation with LACP
802.3ae 10 Gigabit Ethernet (10GBASE-X)
802.3at PoE (N3224P-ON, N3248P-ON, N3208PX-ON, N3224PX-ON,

N3248PX-ON)
802.3bt PoE (N3208PX-ON, N3224PX-ON, N3248PX-ON)
802.3AX LAG Load Balancing
Dell Multi-Chassis LAG (MLAG)
Dell Policy Based Forwarding
802.3az Energy Efficient Ethernet (EEE)
802.3u Fast Ethernet (100BASE-TX) on management ports
802.3x Flow Control
802.3z Gigabit Ethernet (1000BASE-X)
802.3bz 1G/2.5G/5G/10G
ANSI LLDP-MED (TIA-1057)
Dell EqualLogic iSCSI Auto-configuration
MTU 9,216 bytes
General Internet protocols
General Internet protocols are supported. For a detailed list, please contact your Dell Technologies representative.
General IPv4 protocols
General IPv4 protocols are supported. For a detailed list, please contact your Dell Technologies representative.
General IPv6 protocols
General IPv6 protocols are supported. For a detailed list, please contact your Dell Technologies representative.
Layer 3 functionality
1058 RIPv1
1724 RIPv2 MIB Extension
1765 OSPF DB overflow
1850 OSPF MIB
2082 RIP-2 MD5 Auth
2328 OSPFv2
2338 VRRP
2370 Opaque
Dell Policy Based Routing
2453 RIPv2
2740 OSPFv3
2787 VRRP MIB
3101 NSSA
3137 OSPF Stub Router Advert
3623 Graceful Restart
3768 VRRP
4271 BGP
5187 OSPFv3 Graceful Routing Restart
Multicast
1112 IGMPv1
2236 IGMPv2
2365 Admin scoped IP
2710 MLDv1
2932 IPv4 MIB
2933 IGMP MIB
3810 MLDv2
3973 PIM-DM
4541 IGMP v1/v2/v3 Snooping and Querier
5060 PIM MIB
5061 PIM MIB
3376 IGMPv3
Dell Static IP Multicast
Draft-ietf-pim-sm-bsr-05
Draft-ietf-idmr-dvmrp-v3-10 DVMRP
Draft-ietf-magma-igmp-proxy-06.txt
IGMP/MLD Proxying
Draft-ietf-magma-igmpv3-and-routing-05.txt
draft-ietf-idmr-dvmrp-mib-11
draft-ietf-magma-igmp-mib-05
draft-ietf-pim-bsr-mib-06
IEEE 802.1ag draft 8.1 – Connectivity Fault Management (CFM)
IEEE 802.1p GMRP Dynamic L2 Multicast Registration

Quality of service

2474	DiffServ Field
2475	DiffServ Architecture
2597	Assured Fwd PHB
Dell	Port Based QoS Services (TCP/UDP) Mode
Dell	Red/WRED
Dell	Flow Based QoS Services
Dell	Audio Video Bridging Mode (IPv4/IPv6)
Dell	UDLD
2697	srTCM
4115	trTCM

Network Management and Security

Dell	L4 Trusted Mode
1155	SMIPv1
1157	SNMPv1
1212	Concise MIB Definitions
1213	MIB-II
1215	SNMP Traps
1286	Bridge MIB
1442	SMIPv2
1451	Manager-to-Manager MIB
1492	TACACS+
1493	Managed objects for Bridges MIB
1573	Evolution of Interfaces
1612	DNS Resolver MIB Extensions
1643	Ethernet-like MIB
1757	RMON MIB
1867	HTML/2.0 Forms with file upload extensions
1901	Community-based SNMPv2
1907	SNMPv2 MIB
1908	Coexistence between SNMPv1/v2
2011	IP MIB
2012	TCP MIB
2013	UDP MIB
2068	HTTP/1.1
2096	IP Forwarding Table MIB
2233	Interfaces Group using SMIPv2
2246	TLS v1
2271	SNMP Framework MIB
2295	Transport Content Negotiation
2296	Remote Variant Selection
2576	Coexistence between SNMPv1/v2/v3
2578	SMIPv2
2579	Textual Conventions for SMIPv2
2580	Conformance Statements for SMIPv2
2613	RMON MIB
2618	RADIUS Authentication MIB
2620	RADIUS Accounting MIB
2665	Ethernet-like Interfaces MIB
2666	Identification of Ethernet chipsets
2674	Extended Bridge MIB
2737	ENTITY MIB
2818	HTTP over TLS
2819	RMON MIB (groups 1, 2, 3, 9)
2856	Text Conv. For High Capacity Data Types
2863	Interfaces MIB
2865	RADIUS
2866	RADIUS Accounting
2868	RADIUS Attributes for Tunnel Prot.
2869	RADIUS Extensions

3410	Internet Standard Mgmt. Framework
3411	SNMP Management Framework
3412	Message Processing and Dispatching
3413	SNMP Applications
3414	User-based security model
3415	View-based control model
3416	SNMPv2
3417	Transport Mappings
3418	SNMP MIB
3577	RMON MIB
3580	802.1X with RADIUS
3737	Registry of RMON MIB
4086	Randomness Requirements
4113	UDP MIB
4251	SSHv2 Protocol
4252	SSHv2 Authentication
4253	SSHv2 Transport
4254	SSHv2 Connection Protocol
4419	SSHv2 Transport Layer Protocol
4521	LDAP Extensions
4716	SECSH Public Key File Format
5246	TLS v1.2
6101	SSL
6398	IP Router Alert
Dell	Enterprise MIB supporting routing features

draft-ietfhubmib- etherifmib- v3-00.txt (Obsoletes RFC 2665)

Other certifications

N-Series products have the necessary features to support a PCI compliant network topology.

Regulatory, environment and other compliance

Safety and emissions

Australia/New Zealand: ACMA RCA Class A

Canada: ICES Class A; cUL

China: CCC Class A; NAL

Europe: CE Class A

Japan: VCCI Class A

USA: FCC Class A; NRTL UL; FDA 21 CFR 1040.10 and 1040.11

Eurasia Customs Union: EAC Germany: GS mark

Product meets EMC and safety standards in many countries inclusive of USA, Canada, EU, Japan, China. For more country-specific regulatory information, and approvals, please see your Dell Technologies representative.

RoHS

Product meets RoHS compliance standards in many countries inclusive of USA, EU, China, and India. For more country-specific RoHS compliance information, please see your Dell Technologies representative.

EU WEEE

EU Battery Directive

REACH

Energy

Japan: JEL



**Dell
Technologies
Services**

Plan, deploy, manage and support your IT transformation with our top-rated services

Consulting

Dell Technologies Consulting Services provides industry professionals with a wide range of tools and the experience you need to design and execute plans to transform your business.

Deployment

Accelerate technology adoption with ProDeploy Enterprise Suite. Trust our experts to lead deployments through planning, configuration and complex integrations.

Management

Regain control of operations with flexible IT management options. Our Residency Services help you adopt and optimize new technologies and our Managed Services allow you to outsource portions of your environment to us.

Support

Increase productivity and reduce downtime with ProSupport Enterprise Suite. Expert support backed by proactive and predictive artificial intelligence tools.

Education

Dell Technologies Education Services help you develop the IT skills required to lead and execute transformational strategies. Get certified today.

Learn more at
DellTechnologies.com/Services

Learn more at DellTechnologies.com/Networking